



80 Cypress Street, Warwick, RI 02888 ♦ U.S.A.
401-941-3000 ♦ 800-272-7752 ♦ Fax: 1-401-941-0150
info@rbcepoxy.com ♦ www.rbcepoxy.com

♦ TECHNICAL BULLETIN ♦ TECHNICAL BULLETIN ♦ TECHNICAL BULLETIN ♦

WB 204 Air Dry Acrylic Coating

DESCRIPTION:

WB 204 is a clear waterborne acrylic air dry coating which provides a tough, scratch resistant, finish with excellent adhesion to most substrates. WB 204 has excellent moisture resistance, and is a viable alternative to solvent based coatings. This product meets current state and federal restrictions on VOC's. It is also available in a full range of custom colors with gloss ranges from semi gloss to flat.

APPLICATIONS:

- Factory floors
- Concrete and masonry walls
- Plastic toys, and sporting equipment
- Paper, metal and fabric products
- Decorative trims and finishes
- Conformal coating

BENEFITS:

- Dries tack free in less than 15 minutes. Full cure in 6 hrs. @ 70F
- Low VOC level of 120 grams/liter on 1 lb per gallon
- Easily applied with conventional spray equipment, brush or roller
- Easy water clean up

LIQUID CHARACTERISTICS:

Resin Base	Acrylic Emulsion
Viscosity @ 25°C, cps	150-200 cps
Specific Gravity @ 25°C	1.02
Color:	Standard Colors or Custom Upon Request (Semi Gloss to Flat)

STORAGE:

Store in tightly capped plastic containers. DO NOT FREEZE. Shelf life: 6 months.